

3M™ All Weather Flashing Tape 8067

Sticks
fast
at 0-120°F

Stays stuck
at up to 176°F



No primers, no staples, no nonsense

With unique pressure sensitive acrylic adhesive, 3M™ All Weather Flashing Tape 8067 bonds on contact to seal through-wall penetrations at application temperatures from 0°F (-18°C) up to 120°F (49°C). Around windows, doors and other openings in wood frame construction, you save the time and work of primers or staples commonly used to attach many moisture-proofing membranes.

Engineered for handling ease and performance reliability

- High tack to grab fast and tight even on damp surfaces
- Versatile to stick securely to most common building materials even at service temperature up to 176°F (80°C)
- Proprietary backing for long term confidence
 - Seals around nails and staples to prevent moisture intrusion
 - Thin for a reliable and convenient fit into corners and under siding
- Tough to resist punctures and tears during application and service life
- Fast, convenient application
 - No adhesive melting or staining in the summer's heat
 - Split-liner for easy and accurate positioning of tape, especially long lengths
 - Choice of three widths for the coverage you need: 4", 6", 9"
- Resists UV exposure for up to 60 days
- No adverse reaction with many building sealants (preliminary data for synthetic rubber, butyl, polyurethane, silicone and silane terminated hybrids).

3M

3M™ All Weather Flashing Tape 8067

Test Description	Tape Thickness (Backing & Adhesive)	Adhesion to Housewrap* oz/in (N/100mm)	Adhesion to Polyethylene oz/in (N/100mm)	Adhesion to Plywood oz/in (N/100mm)	Nail Sealability before and after Thermal Cycling	Nail Sealability after UV Exposure	Application Temperature Range °F (°C)	Service Temperature Range °F (°C)
Test Method	ASTM 3652	ASTM D-3330 per AAMA 711-05	ASTM D-3330 per AAMA 711-05	ASTM D-3330 per AAMA 711-05	ASTM E331 as modified per AAMA 711-05 Annex 1	ASTM E331 at 137 Pa		Tested per AAMA 711-05
Results	9.5 mils (0.24 mm)	55 oz./in. (60 N/100 mm)	60 oz./in. (66 N/100 mm)	70 oz./in. (77 N/100 mm)	Pass	Pass	0 to 120°F (-18 to 49°C)	-40 to 176°F (-40 to 80°C)

Note: This technical information and data should be considered representative or typical only and should not be used for specification purposes.

* Spun bonded polyethylene



Size	UPC Number	Quantity per case
4 in. x 75 feet	000 511 1531 6203	12
6 in. x 75 feet	000 511 1531 6210	8
9 in. x 75 feet	000 511 1531 6227	4

Technical Information: The technical information, recommendations and other statements contained in this document are based upon tests or experience that 3M believes are reliable, but the accuracy or completeness of such information is not guaranteed.

Warranty, Limited Remedy, and Disclaimer: Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. User is solely responsible for evaluating the 3M product and determining whether it is fit for a particular purpose and suitable for user's method of application. Unless an additional warranty is specifically stated on the applicable 3M product packaging or product literature, 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. If the 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

Limitation of Liability: Except where prohibited by law, 3M will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.



Industrial Adhesives and Tapes Division

3M Center Bldg. 21-1W-10
900 Bush Ave.
St. Paul, MN 55144-1000
1-800-362-3550
www.3M.com/flashingtape

Printed in U.S.A.
© 3M 2008
00-0000.0000.0

3M is a Trademark of 3M Company