

# ARclad® 8326

Electrically Conductive Tape

## General Information

ARclad® 8326 (lt. gray) is a flexible, closed-cell polyolefin foam tape coated on both sides with a permanent acrylic based pressure-sensitive adhesive. Bonds well to many plastics, vinyls, metals, construction materials, including glass and preserved wood. Suggested for mounting muntins to glass doors and windows.

## Features and Benefits

### Features

Quick Stick  
Comformable  
Moisture Resistant  
Easy to Handle  
Weather Resistant  
Chemical Resistant

### Benefits

Readily adheres to clean surfaces  
Conforms to curved and irregular surfaces  
Resists humidity and moist conditions  
Easy to apply by hand, no messy clean-up  
Resists natural elements  
Resists many household window cleaners

## Product Profile

Backing: 1/32" light gray closed-cell polyolefin foam  
Adhesive: AS-98, acrylic based pressure-sensitive adhesive  
Release Liner: ARclad® 8326-11 = 74# kraft paper  
ARclad® 8326-19 = 3 mil blue poly

## Storage and Stability

Service Temperature Range: -20°F to 175°F (-29°C to 79°C)  
Storage: Unconverted, up to one year when stored at 70°F (21°C), 50% R.H.

#### APPLICATION AND STORAGE OF PRESSURE-SENSITIVE ADHESIVE TAPES

Pressure-sensitive adhesive tapes function as a mechanical product; however, the adhesive itself is a chemical composition that can be sensitive to environmental conditions. A purchaser of pressure-sensitive adhesive products should be aware of the shelf life of each product and not purchase more than it can use before the expiration date. Shipping and storage conditions affect shelf life. The optimum storage temperature is 70°F (21°C). Cool, dry storage is recommended.

#### For best results...

- 1.) The surfaces you wish to bond should be clean and free of oil, moisture and dust. If the surface temperature is below 40°F, it may be difficult to achieve a proper bond.
- 2.) Do not use a pressure-sensitive adhesive product where it will be exposed to temperatures lower or higher than those designated for each product. Heat can destroy the effectiveness of the bond and extreme cold can cause the adhesive to harden and not adhere properly.
- 3.) When the tape is applied, use firm hand or lamination pressure to achieve contact between the adhesive and the surface to which it is applied. Hand rollers or nip rollers may be needed for certain products or applications.

Consult your AR sales representative if you need additional information.

#### WARRANTY AND DISCLAIMER

AR expressly warrants to Purchaser that its product, under normal and intended use maintenance and storage, is free from defects in workmanship for twelve (12) months from the date of shipment, unless otherwise stated. **THIS WARRANTY IS GIVEN IN LIEU OF ALL OTHER WARRANTIES. AR MAKES NO WARRANTY AS TO EXPERIMENTAL AND DEVELOPMENTAL SAMPLES OR MATERIALS. AR MAKES NO WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.** No provisions, representations, diagrams, drawings or pictures contained in any product literature, price list, catalogue, purchase order, product data sheet, order acknowledgment, invoice, delivery ticket, or any other communication by AR, including information on AR's website or representations made by AR's employees or agents, constitute express warranties. Results of tests and recommendations included in communications of AR do not constitute express warranties. **SINCE MANY FACTORS MAY AFFECT THE USE AND PERFORMANCE OF AN AR PRODUCT IN A PARTICULAR APPLICATION, INCLUDING, AMONG OTHERS, THE PRODUCT SELECTED FOR USE, THE CONDITIONS IN WHICH THE PRODUCT IS USED, THE TIME AND ENVIRONMENTAL CONDITIONS IN WHICH THE PRODUCT IS EXPECTED TO PERFORM, THE MATERIALS TO BE USED WITH THE PRODUCT, THE SURFACE PREPARATION OF THOSE MATERIALS, AND THE APPLICATION METHOD FOR THE PRODUCT, PURCHASER ACCEPTS RESPONSIBILITY FOR DETERMINING WHETHER AR'S PRODUCT IS FIT FOR A PARTICULAR PURPOSE AND SUITABLE FOR PURCHASER'S METHOD OF APPLICATION.** AR retains the right to modify or change its products if in AR's judgment it is advisable.

Purchaser's exclusive remedy and AR's sole obligation for any breach of warranty is limited to, at AR's option, either: 1) replacement of AR's product, or 2) reimbursement of the purchase price of AR's product. **AR DISCLAIMS ANY OTHER OBLIGATION OR LIABILITIES ARISING OUT OF BREACH OF WARRANTY.** AR will not be liable of any loss, damage, expense or consequential, incidental or special damages of any kind.

<sup>sm</sup>Pressure-sensitive systems. Customer-sensitive solutions. is a service mark of Adhesives Research, Inc.

©2004 Adhesives Research, Inc. Printed in USA.

Internet: [www.adhesivesresearch.com](http://www.adhesivesresearch.com)

#### Adhesives Research, Inc.

400 Seaks Run Road, Glen Rock, PA 17327  
Toll-free: 800-445-6240  
Phone: 717-235-7979  
Fax: 717-235-8320

#### Adhesives Research Ireland Ltd.

Raheen Industrial Estate  
P.O. Box 101  
Limerick Ireland  
Phone: +353 61 300 300  
Fax: +353 61 300 700

#### Adhesives Research Ltd.

P.O. Box 9138 Dunmow  
Essex, CM6 3TE, England  
Phone: +44 (0)1371 865300  
Fax: +44 (0)1371 865380

#### Adhesives Research Pte. Ltd.

1 Science Park Road, #04-10 The Capricorn  
Singapore Science Park 2, Singapore 117528  
Phone: +65 6774 9580  
Fax: +65 6777 7891

#### Adesives Research GmbH

Stefan-George Ring 29, D-81929  
Munchen, Germany  
Phone: +49 (0)89930 86220  
Fax: +49 (0)89930 5184