

30804 SURFACE PROTECTION TAPE

APPLICATION OF FILM

Preferably the protective film should be applied by mechanical means. Best results are obtained at an application temperature between 60°F and 100°F.

PRECAUTIONS

Adhesive properties are susceptible to change due to following parameters: chemical and physical state of the surface to be protected; presence of impurities within or on the substrate; elongation of the film during application; and temperature of surroundings and of substrate.

STORAGE

The film can be stored for six months, in its original packaging and in dry conditions. The rolls should be protected from extremes of temperature and direct sunlight. Out of its container, the film should be protected against dust and other impurities.

TOLERANCE

The thickness of the protective film has to be taken into account for the tolerances of any processing equipment coming into contact with the film.

Tests should be conducted under actual applications conditions.

TECHNICAL DATA

Film Backing	Polyethylene
Color	Black/White
Adhesive type	Rubber/Resin
Adhesion level	Medium
Total tape thickness	3.2 mils
UV resistance	Good
Main applications	Protection of surfaces during mechanical processing. Protection against scratches, abrasion and dirt during storage and transportation.
Typical surfaces	Stainless steel (BA and a range of grit and brush finishes) Anodized aluminum (shiny and matte) Matte plastic substrates (PMMA, polystyrol, PVC)

Note: The above are typical values and should not be used in writing specifications.

For Additional Information on this Product, Call Toll-Free 1-800-755-TAPE.