

## **4058H SURFACE PROTECTION FILM TAPE**

### **APPLICATIONS**

- Protection of high gloss surfaces against mechanical damage (scratches, abrasion, dirt) during storage, transportation and light processing.
- Typical surfaces: polyester, PVDF and other acrylic lacquered plates with a gloss between 20% and 40%. Matte aluminum plates, different matte plastic surfaces. The higher peel level is developed to have a suitable peel off on all more textured and matte surfaces.
- Also very suitable on UPVC window profiles.
- Resists UV-radiation, suitable for outside use.
- 50 micron thick, clear adhesive film.

### **APPLICATION OF FILM**

Preferably the protective film should be applied by mechanical means. Best results are obtained at an application temperature between 15°C and 40°C.

### **PRECAUTIONS**

Adhesive properties are susceptible to change due to following parameters: chemical and physical state of the surface to be protected; presence of impurities within or on the substrate; elongation of the film during application; and temperature of surroundings and of substrate.

### **STORAGE**

The film can be stored for six months, in its original packaging and in dry conditions. The rolls should be protected from extremes of temperature and direct sunlight. Out of its container, the film should be protected against dust and other impurities.

### **TOLERANCE**

The thickness of the protective film has to be taken into account for the tolerances of any processing equipment coming into contact with the film.

Tests should be conducted under actual applications conditions.

### **TECHNICAL DATA**

Thickness	0.05 mm
Color	Clear
Adhesive type	Acrylic
Adhesion level	High
UV resistance	Good
Widths*	200 to 2100 mm
Lengths*	500, 1000, 2000 m

\* Special sizes on request available

**For Additional Information on this Product, Call Toll-Free 1-800-755-TAPE.**