

5057A SURFACE PROTECTION FILM TAPE

APPLICATION OF FILM

Preferably the protective film should be applied by mechanical means. Best results are obtained at an application temperature between 60°F and 100°F.

PRECAUTIONS

Adhesive properties are susceptible to change due to following parameters: chemical and physical state of the surface to be protected; presence of impurities within or on the substrate; elongation of the film during application; and temperature of surroundings and of substrate.

STORAGE

The film can be stored for six months, in its original packaging and in dry conditions. The rolls should be protected from extremes of temperature and direct sunlight. Out of its container, the film should be protected against dust and other impurities.

TOLERANCE

The thickness of the protective film has to be taken into account for the tolerances of any processing equipment coming into contact with the film.

Tests should be conducted under actual applications conditions.

TECHNICAL DATA

Tape thickness	2.0 mils
Film Backing	Polyethylene
Color	Blue
Adhesive type	Acrylic
Adhesion level	Very low
UV resistance	6 months
Typical surface applications	<ul style="list-style-type: none">• High-gloss stainless steel and aluminum, especially reflector grade• High-gloss plastics (PMMA and polycarbonate)• High-gloss lacquered surfaces

5058A SURFACE PROTECTION FILM TAPE

APPLICATION OF FILM

Preferably the protective film should be applied by mechanical means. Best results are obtained at an application temperature between 60°F and 100°F.

PRECAUTIONS

Adhesive properties are susceptible to change due to following parameters: chemical and physical state of the surface to be protected; presence of impurities within or on the substrate; elongation of the film during application; and temperature of surroundings and of substrate.

STORAGE

The film can be stored for six months, in its original packaging and in dry conditions. The rolls should be protected from extremes of temperature and direct sunlight. Out of its container, the film should be protected against dust and other impurities.

TOLERANCE

The thickness of the protective film has to be taken into account for the tolerances of any processing equipment coming into contact with the film.

Tests should be conducted under actual applications conditions.

TECHNICAL DATA

Tape thickness	2.0 mils
Film Backing	Polyethylene
Color	Clear
Adhesive type	Acrylic
Adhesion level	Very low
UV resistance	6 months
Typical surface applications	<ul style="list-style-type: none">• High-gloss stainless steel and aluminum, especially reflector grade• High-gloss plastics (PMMA and polycarbonate)• High-gloss lacquered surfaces

For Additional Information on this Product, Call Toll-Free 1-800-755-TAPE.