

TBP 48 Vinyl Tape

Vinyl Plastic Electrical Tape



Technical Data:	
Backing:	Vinyl Film
Adhesive:	Rubber Based
Thickness:	7.0 mils
Adhesion to Steel:	25 oz/inch
Tensile Strength:	20 lbs/inch
Elongation:	200%
Insulation Class	80°C
Dielectric Strength	9,500 volts

Surface Preparation:

The surface to which the tape is to be applied to should be clean, free of dust, grease, oil and be dry.

Pressure-sensitive adhesive tapes function as a mechanical product. The adhesive however is a chemical composition that can be sensitive depending on the environment it is in. One who purchases a pressure-sensitive adhesive product should be aware of the shelf life and not to purchase the product on after the expiration date. Optimum storage temperature is 70 F with a storage range of 60 F to 80 F. Cool dry storage is recommended. All information and recommendations given by us in good faith are on the basis of practical experience but without warranty. It's essential that the user evaluate the product for a period of time to determine whether it fits a particular purpose and is suitable for the user's method of application.

Description:

TBP 48 UL Vinyl Plastic Electrical Tape is a vinyl backed tape with a rubber based adhesive. TBP 48 meets Government Spec HH-I-595C. This product typically is used in insulating wire splices, harness wrapping and general industrial maintenance applications.

Features & Benefits:

- A Vinyl Plastic Insulating Tape
- Available in a variety of colors
- Designed for applications where good quality and UL listing are required

Applications:

- Insulating Wire Splices
- Harness Wrapping
- General Industrial Maintenance Applications