

TBP 50 Marking Tape Vinyl Splicing Tape



Technical Data:	
Backing:	Vinyl Film
Adhesive:	Natural Rubber Resin
Thickness:	5.0 mils
Adhesion to Steel:	30 oz/inch
Tensile Strength:	18 lbs/inch
Government Spec	PPP-T-66D, Type 1

Surface Preparation:

The surface to which the tape is to be applied to should be clean, free of dust, grease, oil and be dry.

Pressure-sensitive adhesive tapes function as a mechanical product. The adhesive however is a chemical composition that can be sensitive depending on the environment it is in. One who purchases a pressure-sensitive adhesive product should be aware of the shelf life and not to purchase the product on after the expiration date. Optimum storage temperature is 70 F with a storage range of 60 F to 80 F. Cool dry storage is recommended. All information and recommendations given by us in good faith are on the basis of practical experience but without warranty. It's essential that the user evaluate the product for a period of time to determine whether it fits a particular purpose and is suitable for the user's method of application.

Description:

TBP 50 is a premium vinyl tape designed for safety marking and floor splicing. It is available in multiple colors and widths.

TBP 50 satisfies all O.S.H.A marking requirements.

Features & Benefits:

- Highly conformable to all surfaces
- Abrasion Resistant
- Used for Color Coding
- 13 Colors Available:
Black, White, Gray, Clear, Red, Yellow, Dark Blue, Light Blue, Dark Green, Light Green, Orange, Brown, Purple

Applications:

- Color Coding
- Dance Floor Splicing