

TBP 724 Marking Tape

Printable Flatback Paper



Technical Data:	
Tensile Strength:	30 lbs/inch
Thickness:	6.1 mils
Adhesion:	48 oz/inch
Elongation:	3%
Maximum Temp:	150 F
Minimum Temp:	40 F

Surface Preparation:

The surface to which the tape is to be applied to should be clean, free of dust, grease, oil and be dry.

Pressure-sensitive adhesive tapes function as a mechanical product. The adhesive however is a chemical composition that can be sensitive depending on the environment it is in. One who purchases a pressure-sensitive adhesive product should be aware of the shelf life and not to purchase the product on after the expiration date. Optimum storage temperature is 70 F with a storage range of 60 F to 80 F. Cool dry storage is recommended. All information and recommendations given by us in good faith are on the basis of practical experience but without warranty. It's essential that the user evaluate the product for a period of time to determine whether it fits a particular purpose and is suitable for the user's method of application.

Description:

TBP 724 is a printable flatback paper with clean removal adhesive properties.

Features & Benefits:

- Highly visible colors available
- Excellent adhesion for bundling with clean removal
- Writeable surface for marking
- Conformable tape for many surfaces

Applications:

- Exposed Masking to weather / outdoor conditions
- Interior Masking of Windows
- Use on lacquer or PE coated surfaces
- Unfinished wood, wallpaper
- New or unpainted or freshly painted wallboard

