

# TBP 765 Masking Tape

## Utility Grade Crepe Paper Masking Tape

### Natural Color



#### *Description:*

TBP 765 Masking Tape is a general purpose utility grade tape designed to be used on a variety of substrates. It is made up of crepe paper with a very high rubber based blended adhesive.

#### *Features & Benefits:*

- Good Adhesion on variety of substrates
- Flexible
- Easy to Use
- Excellent Quick Stick
- Resists Water & Oil

#### *Applications:*

- General Purpose packaging
- Bundling
- Holding
- Splicing
- Tabbings
- Banding

#### *Surface Preparation:*

The surface to which the tape is to be applied to should be clean, free of dust, grease, oil and be dry.

<u>PHYSICAL PROPERTIES</u>	<u>STANDARD</u>	<u>METRIC</u>
Tensile Strength	20 lbs/in width	35.0N/10mm
Adhesion to Stainless Steel	48 oz/in width	5.25N/10mm
Thickness	5.5 mils	0.14mm
Elongation	8%	8%
Service Temperature Range	50 F to 150 F	10 C to 66 C

#### Standard Widths:

12mm (1/2")  
18mm (3/4")  
24mm (1")

#### Standard Length:

60 yards

Pressure-sensitive adhesive tapes function as a mechanical product. The adhesive however is a chemical composition that can be sensitive depending on the environment it is in. One who purchases a pressure-sensitive adhesive product should be aware of the shelf life and not to purchase the product on after the expiration date. Optimum storage temperature is 70 F with a storage range of 60 F to 80 F. Cool dry storage is recommended. All information and recommendations given by us in good faith are on the basis of practical experience but without warranty. It's essential that the user evaluate the product for a period of time to determine whether it fits a particular purpose and is suitable for the user's method of application.