

TBP Stucco 635 Series

With Synthetic Rubber Adhesive

Red Stucco Tape



Description:

A Heavy Duty Red Polyethylene Tape with a single coat of synthetic rubber based adhesive. Designed for use in numerous applications for protection of surfaces.

Features & Benefits:

- High Quality Materials
- Excellent Wear During Use
- Permanently tacky adhesive allows for bonding in many temperature ranges
- Is a highly conformable tape
- Maintains a watertight seal in all weather conditions
- Good tear characteristics
- High Visibility

Applications:

- Wire Identification
- Surface Protection
- Strapping and Taping of materials
- Masking

Surface Preparation:

The surface to which the tape is to be applied to should be clean, free of dust, grease, oil and be dry.

Technical Data:

Backing Adhesion— Initial Backing to Substrate <i>20 Minutes at Room Temperature</i>	35 oz. / Inch
Peel Adhesion <i>Initial to Substrate 20 Minutes at Room Temperature</i>	60 oz. / Inch
Total Thickness	7.0 Mills
Adhesive Thickness	2.5 Mills
Adhesion to Steel	25 oz. per Inch
Tensile Strength	18 lbs. per Inch
Elongation	80%

Pressure-sensitive adhesive tapes function as a mechanical product. The adhesive however is a chemical composition that can be sensitive depending on the environment it is in. One who purchases a pressure-sensitive adhesive product should be aware of the shelf life and not to purchase the product on after the expiration date. Optimum storage temperature is 70 F with a storage range of 60 F to 80 F. Cool dry storage is recommended. All information and recommendations given by us in good faith are on the basis of practical experience but without warranty. It's essential that the user evaluate the product for a period of time to determine whether it fits a particular purpose and is suitable for the user's method of application.

