

Sika® Cleaner-226

Technical Product Data (typical values)

Color	Transparent liquid
Density (uncured)	6.7 lbs/gal
Flash point	57 °F (14 °C)
Application temperature	product 41 °F to 110 °F (5 °C to 43 °C)
Drying time ¹	10 min at 73 °F / 50% R.H.
Storage	Store in sealed container in a cool dry place
Shelf life (storage below 80 °F (27 °C))	12 months in unopened container

¹⁾ In specific applications, dry times may be different

Description

Sika®-Cleaner 226 is a special adhesion promoting solution for the pretreatment of bonding surfaces prior to bonding or sealing with Sikaflex® products. Sika® Cleaner-226 is manufactured in accordance with ISO 9001/14001 quality assurance system and the Responsible Care Program.

Areas of Application

Sika®-Cleaner 226 improves adhesion and gives a more weather-resistant bond or seal on a variety of substrates, particularly:

- metals
- many plastics
- many types of paints and lacquer finishes.

Do not use Sika®-Cleaner 226 in direct glazing applications.

Please refer to the Surface Preparation Guidelines for specific application information.

Method of Application

Substrate must be clean, dry, free of oil and grease and of sound quality. Thoroughly remove all loose particles and residues. Clean surface with a strong jet of oil-free compressed air or acetone. Apply Sika®-Cleaner 226 with a lint free tissue or paper towel. Allow cleaner to dry 10 minutes but not more than 2 hours before applying adhesive or sealant. If adhesive or sealant cannot be applied within 2 hours of cleaning, repeat application. Reseal container tightly immediately after use.

This product is suitable for experienced professional users only. Tests with actual substrates and conditions have to be performed to ensure adhesion and material compatibility.

Industry



Important Note

Discard any Sika® Cleaner-226 that has become opaque instead of clear.

Limitations

- Never apply to porous substrates.
- Reseal container tightly between use.

Note: Sika®-Cleaner 226 replaces Sika®-Cleaner 205. For further specific application information, please contact our Technical Services Department.

CAUTION: IRRITANT.

Contains isopropyl alcohol. Extremely flammable. Keep away from heat, sparks, flame. Skin, eye, respiratory irritant. Avoid contact with eyes, skin, clothing. May cause dizziness, headache, or other central nervous system effects. Avoid breathing vapor. Use only with adequate ventilation. Use of safety goggles and chemical resistant gloves is recommended. Wash thoroughly after handling. In case of exceedance of PELs, use an appropriate, properly fitted NIOSH/MSHA approved respirator.

HMIS

Health	2
Flammability	3
Reactivity	1
Personal Protection	B

First Aid Measures

In case of eye contact, rinse eyes immediately and thoroughly with water for at least 15 minutes, contact a physician. In case of skin contact, wash with soap and water. For respiratory problems, remove person to fresh air; if symptoms persist, contact a physician. In case of ingestion, consult physician immediately. Remove contaminated clothing.

Further Information

Copies of the following publications are available on our website www.sikaindustry.com:
-Material Safety Data Sheets
-Product Data Sheet
-Sika Primer Chart
-General guidelines for bonding and sealing with Sika products

In case of emergency call:
Chemtrec: 800-424-9300
International: 703-527-3887

For further information and advice regarding transportation, handling, storage and disposal of chemical products, users should refer to the actual Material Safety Data Sheets containing physical, ecological, toxicological and other safety related data. It is highly recommended to read the actual Material Safety Data Sheet before using the product.

**-KEEP OUT OF REACH OF CHILDREN
-NOT FOR INTERNAL CONSUMPTION
-FOR INDUSTRIAL USE ONLY
-KEEP CONTAINER TIGHTLY CLOSED**

Packaging Information

Can	250 ml
-----	--------

Value Basis

All technical data stated on this Product Data Sheet are based on the results of laboratory tests only. Actual measured data in the field may vary due to site specific conditions which are not known to Sika and beyond our control.

Clean Up

In case of spills or leaks, wear suitable protective equipment, contain spill, collect with absorbent material, and transfer to suitable container. Ventilate area. Avoid contact. Dispose of in accordance with current, applicable local, state and federal regulations.

Limited Material Warranty

SIKA warrants this product for one year from date of installation to be free from manufacturing defects and to meet the technical properties on the current Product Data Sheet if used as directed within shelf life. User determines suitability of product for intended use and assumes all risks. Buyer's sole remedy shall be limited to the purchase price or replacement of product exclusive of labor or cost of labor. **NO OTHER WARRANTIES IMPLIED OR EXPRESS SHALL APPLY INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES. SIKA SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY**

OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

Legal Notes/Disclaimer

All information provided by Sika Corporation ("Sika") concerning Sika products, including but not limited to, any recommendations and advice relating to the application and use of Sika products, is given in good faith based on Sika's current experience and knowledge of its products when properly stored, handled and applied under normal conditions in accordance with Sika's instructions. In practice, the differences in materials, substrates, storage and handling conditions, actual site conditions and other factors outside of Sika's control are such that Sika assumes no liability for the provision of such information, advice, recommendations or instructions related to its products, nor shall any legal relationship be created by or arise from the provision of such information, advice, recommendations or instructions related to its products. The user of the Sika product(s) must test the product(s) for suitability for the intended application and purpose before proceeding with the full application of the product(s).

Sika reserves the right to change the properties of its products without notice. All sales of Sika product(s) are subject to its current terms and conditions of sale which are available at www.sikacorp.com or by calling 201-933-8800.

Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's most current Product Data Sheet, product label and Material Safety Data Sheet which are available at www.sikaindustry.com. Nothing contained in any Sika materials relieves the user of the obligation to read and follow the warnings and instruction for each Sika product as set forth in the current Product Data Sheet, product label and Material Safety Data Sheet prior to product use.

Further information available at:
www.sikaindustry.com

Sika Corporation
Industry Division
30800 Stephenson Highway
Madison Heights, MI 48071
USA
Tel. 248 577 0020
Fax 248 577 0810

