

TBP 198

TPP Strapping Tape



Technical Data:	
Backing:	Tensilized Polypropylene
Adhesive:	Rubber
Adhesion:	53 oz/inch
Elongation:	35%
Tensile:	200 lbs/inch

Surface Preparation:

The surface to which the tape is to be applied to should be clean, free of dust, grease, oil and be dry.

Pressure-sensitive adhesive tapes function as a mechanical product. The adhesive however is a chemical composition that can be sensitive depending on the environment it is in. One who purchases a pressure-sensitive adhesive product should be aware of the shelf life and not to purchase the product on after the expiration date. Optimum storage temperature is 70 F with a storage range of 60 F to 80 F. Cool dry storage is recommended. All information and recommendations given by us in good faith are on the basis of practical experience but without warranty. It's essential that the user evaluate the product for a period of time to determine whether it fits a particular purpose and is suitable for the user's method of application.

Description:

TBP 198 is a TPP (tensilized polypropylene) film backed with a natural rubber adhesive system known for reinforcing and its outstanding strength

Features & Benefits:

- Extremely high longitudinal strength
- Low Elongation
- High Strength rubber adhesive system
- Good heat and cold –resistance properties
- Suitable for outside use

Applications:

- Aluminum Extrusion Wrapping
- Bonding of Heavy Duty Pipes
- End-Tabbing of light to medium gauge rolled steel and finished metals
- Heavy Duty Reinforcing