

# TBP 90 Duct Tape

## Light Utility Grade



Technical Data:	
<b>Backing:</b>	2.0 Mil PE Film
<b>Reinforcement:</b>	PET Cloth
<b>Adhesive:</b>	Natural Rubber/Resin
<b>Adhesion to Steel:</b>	44 oz/inch
<b>Elongation:</b>	17%
<b>Tensile:</b>	18 lbs/inch
<b>Colors:</b>	Silver, White, Black

### *Surface Preparation:*

The surface to which the tape is to be applied to should be clean, free of dust, grease, oil and be dry.

Pressure-sensitive adhesive tapes function as a mechanical product. The adhesive however is a chemical composition that can be sensitive depending on the environment it is in. One who purchases a pressure-sensitive adhesive product should be aware of the shelf life and not to purchase the product on after the expiration date. Optimum storage temperature is 70 F with a storage range of 60 F to 80 F. Cool dry storage is recommended. All information and recommendations given by us in good faith are on the basis of practical experience but without warranty. It's essential that the user evaluate the product for a period of time to determine whether it fits a particular purpose and is suitable for the user's method of application.

### *Description:*

TBP 90 Duct Tape is blend of polyester cloth and polyethylene film with an aggressive natural rubber adhesive.

### *Features & Benefits:*

- Easily Conforms to Irregular Surfaces
- Quick Stick
- Economically priced

### *Applications:*

- Packaging
- Wrapping & Sealing
- Binding & Bundling
- General Purpose Maintenance