



PRODUCT INFORMATION

tesa 4298
High-Performance Non-Staining Tensitized Polypropylene Tape

Product Description: tesa 4298 is a high performance non-staining tensitized polypropylene strapping tape with a natural rubber adhesive system. tesa 4298 is a specially designed tape which is stain and adhesive transfer resistant. It features extra high tack, high adhesion and chemical resistance. It is waterproof and non-toxic.

- Applications:**
- Closing, holding and securing in the automotive, appliance, furniture and office equipment, industries
 - “L” and “C” clipping
 - Available on spool rolls
 - Clear version used for handle reinforcement

Technical Data:
(typical values)

Backing:	Tensitized Polypropylene	Adhesive:	Highly Cured Natural Rubber
Tensile Strength:	163 lbs/in 723.9 N/25mm	Elongation at Break:	35%
Total Thickness:	4.6 mils 0.116mm	Color:	Ivory, Blue, Clear, White
Adhesion (steel)	61 oz/in 17 N/25mm	Temperature Resistance:	160° F 70° C

tesa tape inc.
5825 Carnegie Blvd
Charlotte, NC 28209
800-426-2181 Fax: 800-852-8831

tesa self-adhesive tapes are used successfully in many sectors to solve a variety of problems. Our publications contain numerous examples of such uses, intended to help towards a solution of your particular problems. Each tesa product has been developed for a particular range of applications. Nevertheless, experience has shown that even for one and the same objective, the exact requirements may differ from case to case. We, therefore, recommend that you carry out your own tests in each case, to confirm that the tesa self-adhesive tape which you envisage using is appropriate for your particular application. Our Application Engineers will be happy to assist. All information and recommendations are given by us in good faith, on the basis of practical experience, but without warranty.